

**Zoznam svietidiel pre Belianskú jaskyňu**

LED Svietidlá			
Pos.	Objednávkové číslo	Popis svietidla	Počet
1	CL-LQP-04	LED projektor 12W seria LQP; STUDENA BIELA; 9 LED Cree XP-E; Ellipse Hor. (10x45) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	10
2	CL-LSQ-34	LED svietidlo 1,5W seria LSQ; TEPLA BIELA; 1 LED Cree XP-E; Narrow (10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m; nova modifikacia	5
3	CL-LSQ-01	LED svietidlo 3W seria LSQ; STUDENA BIELA; 2 LED Cree XP-E; Narrow (10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	7
4	CL-LQP-27	LED projektor 12W seria LQP; TEPLA BIELA; 9 LED Cree XP-E; Medium (30) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	3
5	CL-LSQ-16	LED svietidlo 3W seria LSQ; TEPLA BIELA; 2 LED Cree XP-E; Medium (30) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	5
6	CL-LQP-26	LED projektor 12W seria LQP; TEPLA BIELA; 9 LED Cree XP-E; Narrow (10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	2
7	CL-LST-01	LED svietidlo 1W seria LST; STUDENA BIELA; 10 LED Cree CLA-1A; Flood angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m; 2x tienidlo	155
8	CL-LSQ-18	LED svietidlo 3W seria LSQ; TEPLA BIELA; 2 LED Cree XP-E; Narrow (10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	3
9	CL-LSQ-29	LED svietidlo 3W seria LSQ; NEUTRALNE BIELA; 2 LED Cree XP-E; Ellipse Vert. (45x10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m; nova modifikacia	6
10	CL-LSQ-24	LED svietidlo 1,5W seria LSQ; NEUTRALNE BIELA; 1 LED Cree XP-E; Narrow (10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	3
11	CL-LSQ-31	LED svietidlo 1,5W seria LSQ; NEUTRALNE BIELA; 1 LED Cree XP-E; Ellipse Vert. (45x10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m; nova modifikacia	2
12	CL-LSQ-36	LED svietidlo 1,5W seria LSQ; TEPLA BIELA; 1 LED Cree XP-E; Ellipse Vert. (45x10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m; nova modifikacia	2
13	CL-LQP-28	LED projektor 12W seria LQP; TEPLA BIELA; 9 LED Cree XP-E; Wide (40) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	9
14	CL-LQP-23	LED projektor 12W seria LQP; NEUTRALNE BIELA; 9 LED Cree XP-E; Ellipse Vert. (45x10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	6
15	CL-LQP-21	LED projektor 12W seria LQP; STUDENA BIELA; 9 LED Cree XP-E; Ellipse Vert. (45x10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	11
16	CL-LQP-16	LED projektor 12W seria LQP; NEUTRALNE BIELA; 9 LED Cree XP-E; Ellipse Hor. (10x45) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	10
17	CL-LSQ-11	LED svietidlo 3W seria LSQ; STUDENA BIELA; 2 LED Cree XP-E; Ellipse Vert. (45x10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	4
18	CL-LSQ-04	LED svietidlo 3W seria LSQ; STUDENA BIELA; 2 LED Cree XP-E; Ellipse Hor. (10x45) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	5
19	CL-LQP-01	LED projektor 12W seria LQP; STUDENA BIELA; 9 LED Cree XP-E; Narrow (10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	16
20	CL-LSQ-33	LED svietidlo 1,5W seria LSQ; STUDENA BIELA; 1 LED Cree XP-E; Wide (40) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m; nova modifikacia	5
21	CL-LSQ-26	LED svietidlo 1,5W seria LSQ; STUDENA BIELA; 1 LED Cree XP-E; Ellipse Hor. (10x45) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	3
22	CL-LQP-13	LED projektor 12W seria LQP; NEUTRALNE BIELA; 9 LED Cree XP-E; Narrow (10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	16
23	CL-LQP-14	LED projektor 12W seria LQP; NEUTRALNE BIELA; 9 LED Cree XP-E; Medium (30) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	35
24	CL-LSQ-25	LED svietidlo 1,5W seria LSQ; NEUTRALNE BIELA; 1 LED Cree XP-E; Medium (30) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	10
25	CL-LSQ-08	LED svietidlo 3W seria LSQ; NEUTRALNE BIELA; 2 LED Cree XP-E; Ellipse Hor. (10x45) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	3
26	CL-LSQ-05	LED svietidlo 3W seria LSQ; NEUTRALNE BIELA; 2 LED Cree XP-E; Narrow (10) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	5
27	CL-LQP-03	LED projektor 12W seria LQP; STUDENA BIELA; 9 LED Cree XP-E; Wide (40) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	31
28	CL-LSQ-03	LED svietidlo 3W seria LSQ; STUDENA BIELA; 2 LED Cree XP-E; Wide (40) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	18
29	CL-LSQ-06	LED svietidlo 3W seria LSQ; NEUTRALNE BIELA; 2 LED Cree XP-E; Medium (30) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	76
30	CL-LSQ-02	LED svietidlo 3W seria LSQ; STUDENA BIELA; 2 LED Cree XP-E; Medium (30) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	25
31	CL-LQP-02	LED projektor 12W seria LQP; STUDENA BIELA; 9 LED Cree XP-E; Medium (30) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	55
32	CL-LQP-15	LED projektor 12W seria LQP; NEUTRALNE BIELA; 9 LED Cree XP-E; Wide (40) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	50
33	CL-LSQ-07	LED svietidlo 3W seria LSQ; NEUTRALNE BIELA; 2 LED Cree XP-E; Wide (40) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m;	63
34	CL-LSQ-32	LED svietidlo 1,5W seria LSQ; NEUTRALNE BIELA; 1 LED Cree XP-E; Wide (40) angle; napätie: 15...35VDC; ovládanie: PWM/DIM; kabel 3 m; nova modifikacia	17

### Riadiace jednotky a iné

Objednávkové			
Pos.	Číslo	Popis	Počet
35	CL-CP1-06	Tlacidlova ovladacia jednotka; 2 tlačidlo; w/ radioprijimac; vstup/vystup: 2xPG11	1
36	CL-CP1-01	Tlacidlova ovladacia jednotka; 4 tlačidlo; w/o radioprijimac; vstup/vystup: 2xPG11	6
37	CL-CN1-03	LED svetelno ovladacia jednotka at 1616; w/o radioprijimac; vstup/vystup: 2xPG7+1xM20+1xPG11	6
38	CL-RR-01	Radioreceiver jednotka ;	6
39	CL-CN1-01	LED svetelno ovladacia jednotka at 1616 ; w/o radioprijimac; vstup/vystup: 2xPG7+1xM20+8xPG11	10
40	CL-CP1-02	Scenograficka ovladacia jednotka; 4 tlačidla; w/ radioprijimac; vstup/vystup: 2xPG11	6
41	CL-MMC-01	Multimedialne ovladanie centrum;	1
42	CL-SPK-01	Reproduktor 50VA ;	6
43	CLRS-01	Zonovy modul ;	8
44	CL-GP1-01	Dialkove ovladanie	10
45	ACRM-02-01	Radiovy prijimac ;	2
46	CL-RSU-01	Prevodova jednotka USB-RS485-DMX; IP65	1
Príslušenstvo			
Objednávkové			
Pos.	Číslo	Popis	Total
47	CL-BL1-02	Držiak pre LSQ, MSQ, ESQ seria, L=150mm (grey plastic); 4x screws	240
48	CL-BL4-01	Držiak pre LQP, MQP, EQP seria, L=150mm (sivy plat); 4x screws	233
49	CL-DBI-02	KONEKTOR I 3P BLIND D7-13.5 IP68	700
50	CL-DBT-02	Type "T" 3-vyvodovy konektor IP67 kabel D 6-7,5mm	500
51	UE01218771	Tyco Gurosil-Gel 250ml	100
52	CL-BR1-01	Teleskopicky držiak pre LED svietidlo	100
53	CL-BR2-01	Držiak svietidla LED	300